



A Subsidiary of Garland Industries

FasTape SRA-W

DESCRIPTION

Low Density Polyethylene Film Tape - 9.0 mil - Synthetic Rubber Based Adhesive remains permanently tacky and bonds well to most surfaces over a wide range of temperatures; excellent low temperature bond. Tough polyethylene backing offers good abrasion and tear resistance. Highly conformable, waterproof and resistant to chemical deterioration.

APPLICATIONS

Ideal for polyethylene splicing; patching/repairing poly sheeting used in boating and RV industry; surface protection & electroplate masking; wire identification; packaging; etc. Works well in most applications where a low thread count polyethylene coated cloth tape is being used.

TECHNICAL DATA

Properties	Value
Total Thickness	9.0 mil (0.229 mm)
Tensile Strength	22 lbs/inch width
Elongation	100%
Adhesion to Steel	60 oz/inch
Adhesion to Backing	35 oz/inch
Moisture Vapor Transmission	0.4 grams/100 sq. in/24 hrs.
Color	White
Format	4" x 36 yd
Core	3"

The information and recommendations discussed in this publication are believed to be correct. The ASTM testing is conducted by an independent accredited laboratory. No statement should be construed as a recommendation for any use, which would violate any patent rights. This document is not a guarantee of a warranty, if approved by GMX, Inc., a performance warranty may be granted.